



P	LTR	DESCRIPTION	DATE	OWN	APVD
NC		NEW RELEASE PER E.O. P20445	26FEB2010	AM	RDR
A		REVISED PER ECO-14-019072	23FEB2015	JA	DM
A1		REVISED PER ECO-16-006700	10MAR2016	CS	DM
A2		REVISED PER PCN E-16-012386	01MAR2017	DD	DM

6. PART MODIFICATION:
ELIMINATES JUMPER SEAL PLUG AND CONTACT

5. RECEPTACLE IS SUPPLIED WITH DUST CAP (2415-001-2405).

4. NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.

3. MATERIAL: RECEPTACLE HOUSING: PA66 GF10 (BLACK)
RETAINING RING: PA66 GF10 (GREEN, BLUE)
GROMMET: SILICONE (ORANGE-RED)

2. SEE 0425-021-0000 APPLICATION SPECIFICATION
A. RECOMMENDED WIRE INSULATION RANGE
B. CONTACT REMOVAL TOOLS
C. RECOMMENDED MOUNTING HOLE & PANEL THICKNESS
D. MOUNTING HARDWARE & MOUNTING TORQUE

1. THIS RECEPTACLE MATES WITH HDP26-24-91SX-XXXX PLUG
X = SEAL TYPE (N,T,E)
XXXX = ALL MODIFICATIONS

7. DATE CODE: IDENTIFIES THE YEAR, MONTH, DAY AND HOUR OF ASSEMBLY.
YEAR: FIRST AND SECOND DIGITS. (14 = 2014)
MONTH: THRID DIGIT, EXCLUDING 1. A = JAN., B = FEB., C = MARCH... (K = OCTOBER)
DAY: FOURTH AND FIFTH DIGITS (14 = 14th DAY)
HOUR: SIXTH AND SEVENTH DIGITS (11 = 11AM)

TE INTERNAL PN	DEUTSCH PN
HDP24-24-91PN-P064	HDP24-24-91PN-P064
2301337-1	HDP24-24-91PE-P064

TE Connectivity

RECEPTACLE, THREADED
SIZE 24
HDP SERIES

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	23FEB2010
		CWR	26FEB2010
		APVD	26FEB2010
DIMENSIONS: INCHES [mm]		PRODUCT SPEC	0425-021-0000
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC	2
0 PLC	±	WEIGHT	56.56g
1 PLC	±	SIZE	A3
2 PLC	± .015 [0.38]	CAGE CODE	4AFU8
3 PLC	±	DRAWING NO	C=HDP24-24-91PX-P064
4 PLC	±	RESTRICTED TO	-
ANGLES	±0° 30' 0"	SCALE	2:1
MATERIAL	N/A	SHEET	1 OF 1
FINISH	N/A	REV	A2

NOTES: