

4

3

2

1

THIS DRAWING IS UNPUBLISHED

RELEASED FOR PUBLICATION

2013

© COPYRIGHT 2013 BY TE CONNECTIVITY.

ALL RIGHTS RESERVED.

LOC - -

DIST - -

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	B	REVISED AND REDRAWN PER E.O P16261	17SEP1999	-	RDR
	C	REVISED PER E.O P17741	27DEC2002	-	RDR
	D	REVISED PER E.O. P21133	29SEP2011	-	RDR
	D1	REVISED PER ECO-14-002953	29JAN2014	PV	DM

5. MATERIAL: PLUG HOUSING AND WELD RING: PA 15%GF (GREY)
GROMMET: SILICONE (RED)

4. OVERALL DIMENSION DOES NOT INCLUDE RUBBER GROMMET.

3. THIS PLUG MATES WITH FOLLOWING RECEPTACLES (X = SEAL TYPE, XXXX = ALL MODIFICATIONS)
HD10-3-96PX-XXXX AND HD14-3-96PX-XXXX

2. SEE DRAWING 0425-015-0000 FOR CONTACT AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS.

1. SEE TABLE FOR USABLE WIRE RANGE AND INSULATION RANGES.

CONTACT SIZE	MINIMUM O.D.	MAXIMUM O.D.	WIRE RANGE [mm ²]
16	.100 [2.54]	.150 [3.81]	14-20 AWG [2.0-.50]

NOTES:

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. HAYNES 23AUG1999		
DIMENSIONS: INCHES [mm]		CHK I. GRANTCHAROVA 17SEP2013		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD D. MEYER 19SEP2013	NAME PLUG CONNECTOR HD10 SERIES 3-96 ARRANGEMENT COLOR: GREY	
		PRODUCT SPEC -	SIZE A3 CAGE CODE 00779 DRAWING NO. HD16-3-96S RESTRICTED TO -	
MATERIAL 5		APPLICATION SPEC -	WEIGHT 14.15 (g)	
FINISH -		Customer Drawing	SCALE 2:1 SHEET 1 OF 1 REV D1	

1470-19 (3/11)